

## DVR- F1104

4CH/1 SATA DVR




## KEY FEATURES

- 1 SATA (Maximum support 6T B)
- Support AHD / TVI 720P / 1080P
- Support VGA, HDMI 1080N HD output
- Video Compression H.264 High Profile
- 4Ch Audio Input/ 1 Ch Audio Output

# DVR- F1104 4CH/1 SATA DVR

## DIMENSION



## INTERFACE



## SPECIFICATION

### VIDEO

Video Compression	H.264 High Profile
Encode Ability	4ch*1080N@15fps
Decode Ability	4ch *1080N@15fps
Video Input (Pure Analog)	4ch*720P
	Support 4ch*1080P
Mixed:	2ch*AHD(720P)+2ch*TVI(720P)
	2ch*AHD(1080P)+2ch*IPC(720P)
Support	2ch*AHD(1080P)+2ch*TVI(1080P)
	2ch*AHD(1080P)+2ch*IPC(1080P)
Pure Network	4ch*720P
	Support 4ch*1080P

### AUDIO

Audio Compression	G.711A
Two Way Audio	Support

### RECORD AND PLAYBACK

Hard Drive	1 SATA (Maximum support 6TB)
Record	Manual/Event/Timer
Playback	4ch(pure local input mode)

### STORAGE & BACK UP

Space Occupation	960H:12~20G/ day*channel
	720P:~20G/ day*channel
	1080P 20~30G/ day*channel
	Audio:691.2M/ day*channel
Backup Mode	USB HDD

### INTERFACE

Video Input	4ch BNC (AHD/TVI/CVBS)
Video Output	1ch VGA,1ch HDMI
Audio Input	4ch RCA
Audio Output	1ch RCA
Network Interface	1 RJ45 10M/100M Adaptive Ethernet Port
PTZ Control	RS485, Support Multiple PTZ Protocols
USB	2 USB

### GENERAL

Power	DC12V/2A
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Dimension	255mm(L) x 255mm(W) x 45mm(H)