

Product Highlights

Flexible Mobile Broadband

3G/4G mobile connectivity lets you take your broadband connection with you wherever you go

Internet Access For All Your Devices

Share your mobile Internet connection with your laptop PC, smart phone, tablet, and with others through a high-speed wireless network

Active Security Features

Dual active firewalls and WPA/WPA2 wireless encryption help protect your network from intrusions and prying eyes



DWR-920

Wireless N300 4G LTE Router

Features

Connectivity

- Uses a SIM/UICC card to connect to the Internet
- Two 10/100 Ethernet LAN ports to connect wired devices
- · Optional WAN port for fixed line broadband
- Support WAN to 4G Failover
- · 802.11n/g/b wireless

Security Features

- WPA/WPA2 Wi-Fi security protocols provide the latest in wireless security
- Wi-Fi Protected Setup (WPS) for one-touch secure setup with other Wi-Fi devices

Convenient

- · Intuitive built-in web interface
- LED indicators to check the real-time status of your network

The D-Link DWR-920 Wireless N300 4G LTE Router is a cost-efficient solution that allows users to access mobile broadband networks. Once connected, users can transfer data, stream media, and send SMS messages. Simply insert your 3G/4G SIM card and share your Internet connection through a secure wireless network or by using any of the two 10/100/1000 Ethernet ports.

Fast Mobile Internet

The DWR-920 lets you connect to your 3G/4G mobile connection with fast downlink speeds of up to 100 Mbps and uplink speeds up to 50 Mbps, giving you the speed you need for fast, responsive Internet access. Surf the web with ease and stream music and video over the Internet to your PCs and mobile devices.

Active Security Features

The DWR-920 utilizes dual active firewalls (SPI and NAT) to prevent potential attacks over the Internet. WPA/WPA2 wireless encryption keeps your wireless network secure and your traffic safe, allowing you to share your 3G/4G connection without worrying about unauthorized users accessing yournetwork.

Easy to Set Up and Use

The DWR-920 can be installed quickly and easily almost anywhere. It can be configured through almost any web browser without the need for special software. This router makes it possible to stay connected, even when conventional broadband services are unavailable.




DWR-920 Wireless N300 4G LTE Router

YourNetworkSetup



Back View



Bottom View



General		
 LTE Bands: Release 10, Cat 4: Band 1/3/5/7/8/20/38/40 Pentaband UMTS/HSPA/HSPA+/DC-HSPA+ Bands 1/5/8 (850/900/2100) 	• Quadband GSM/GPRS/EDGE • 850/900/1800/1900	
LTE ModeDownlink: Up to 150 MbpsUplink: Up to 50 Mbps	 DC-HSPA Mode Downlink: Up to 42 Mbps Uplink: Up to 5.76 Mbps 	
• IEEE 802.11n/g/b • IEEE 802.3i	• IEEE 802.3u	
 Up to 300 Mbps with 802.11n clients 6/9/11/12/18/24/36/48/54Mbpsin 802.11g mode 	• 1/2/5.5/11 Mbps in 802.11b mode	
 64/128-bitWEP (Wired Equivalent Privacy) WPA & WPA2 (Wi-Fi Protected Access) 	• WPS (Wi-Fi Protected Setup)	
Network Address Translation (NAT)	Stateful Packet Inspection (SPI)	
 L2TP/PPTP/IPSec VPN Passthrough User configurable multi-WAN Port forwarding 	 DMZ (Demilitarized Zone MAC Filter Support WAN to 4G Failover 	
	Release 10, Cat 4: Band 1/3/5/7/8/20/38/40 Pentaband UMTS/HSPA/HSPA+/DC-HSPA+ Bands 1/5/8 (850/900/2100) LTE Mode Downlink: Up to 150 Mbps Uplink: Up to 50 Mbps IEEE 802.11n/g/b IEEE 802.3i Up to 300 Mbps with 802.11n clients 6/9/11/12/18/24/36/48/54Mbpsin 802.11gmode 64/128-bitWEP (Wired Equivalent Privacy) WPA & WPA2 (Wi-Fi Protected Access) Network Address Translation (NAT) L2TP/PPTP/IPSec VPN Passthrough User configurable multi-WAN	

DWR-920 Wireless N300 4G LTE Router

Physical			
Device Interfaces	 Two10/100 Ethernet LAN ports Configurable WAN (RJ-45) port Wireless N 	Standard Mini-SIM/UICCslotTwo detachable 3G/4G antennas	
LED Status Indicators	Power LAN WLAN	Internet Signal Strength	
Dimensions	· 121 x 117.3 x 43.5 mm (4.76 x 4.62 x 1.71 in)	• 121 x 117.3 x 43.5 mm (4.76 x 4.62 x 1.71 in)	
Weight	• 205 g (0.45 lbs)		
Temperature	• Operating: 0 to 40 °C (32 to 104 °F)	• Storage: -10 to 70 °C (14 to 158 °F)	
Humidity	· Operating: 10% to 90% non-condensing	Storage: 0 to 95% non-condensing	
Certifications	• CE		
Order Information			
Part Number	Description		
DWR-920	Wireless N300 4G LTE Router		

 $^{^1}$ Supported frequency bands are dependent on regional variants and may not be available in all markets. 2 Data rates are theoretical. Data transfer rate depends on network capacity and signal strength.

